

PFWDTG



Issued in accordance with the Construction Products Regulation (CPR) 305/2011/EU.
pgb-Europe nv hereby declares that the products mentioned below comply with the requirements of:

EN 14592 2008+A1 2012 – Timber structures - Dowel-type fasteners

1. *Unique identification code of the product-type:*
PFWDTG A4
2. *Type or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*
see annex 1 to this document
3. *Intended uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer:*

Generic type:	Tropical wood screw "PFS" with double thread, reduced countersunk head with 4 ribs, T-drive recess.
Material:	Stainless steel A4 grade 70
Service class:	Service class 3 according to EN 1995-1-1
Fire resistance:	NPD
Reaction to fire:	Classification A1 according to EN13501-1
Intended use:	Mechanical fasteners for the fastening of wooden constructions like terraces and deckings

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):*
pgb-Europe nv – Gontrode Heirweg 170 – 9090 Melle – Belgium
5. *Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):*
NOT RELEVANT
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
System 3
7. *In case of the declaration of performance concerning a construction product covered by a harmonized*

standard: EN 14592:2008 +A1-2012
performed by: HFB Engineering GMBH
Zschortauer Straße 42
04129 Leipzig
under system: 3
and issued: Initial Type Test report n° 311002542/1/2017

DECLARATION OF PERFORMANCE

8. In case of the declaration of performance concerning a construction product for which European Technical Assessment has been issued:

NOT RELEVANT

9. Declared performance:

Essential characteristics		Performance
		Ø 5
Characteristic yield moment $M_{y,k}$	[Nmm]	7150
Characteristic withdrawal parameter $f_{ax,k}$	[N/mm ²]	41,2 ¹
Wood density	ρ_k [kg/m ³]	749
Characteristic head pull-through parameter $f_{head,k}$	[N/mm ²]	57,8
Wood density	ρ_k [kg/m ³]	774
Characteristic tensile capacity $f_{tens,k}$	[kN]	8,17
Characteristic torsional strength $f_{tor,k}$	[Nm]	6,47
Characteristic torsional resistance $R_{tor,k}$	[Nm]	5,54

Tested according to Harmonized Technical Specification EN 14592 2008+A1:2012.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Place and date of issue	Signature
Melle, 27/11/2017	nv pgb-Europe sa Gontrode Heirweg 170 9090 MELLE BE 0425 888 396 

¹ Screwed in at 35mm.

DECLARATION OF PERFORMANCE

Annex 1 : Product overview



DoP: PWDTG102



Ø [mm]	l [mm]	Art. Nr.	EAN code	TX	dk [mm]		
STANDARD PACKING - STANDAARDVERPAKKING - EMBALLAGE STANDARD - NORMALPACKUNG							
5,0	50	PWDTGG50050 A4	5410439474351	TX 25	7,5	200	4800
	60	PWDTGG50060 A4	5410439474368	TX 25	7,5	200	3200
	70	PWDTGG50070 A4	5410439474375	TX 25	7,5	200	3200
	80	PWDTGG50080 A4	5410439474900	TX 25	7,5	200	3200